



## Re-Board® Fire Retardant

Re-board® Fire Retardant is the only EuroClass C certified rigid paper-board. It is incredibly lightweight yet exceptionally strong and fully recyclable. The unique engineered fluted core of Re-board® ensures excellent planar flatness combined with design flexibility to create almost any shape.

### Printing and Finishing

Re-board® Fire Retardant can be digitally printed or finished with decorative laminates to achieve stunning results. It is a versatile board good printability and high performance. The unique engineered fluted core enables a Re-board® sheet to be rapidly cut into any conceivable shape.



### Method

Underneath the fine top layer in Re-board® Fire Retardant hides a thin aluminum foil that makes the board resistant to fire and ignition.

### Euroclass C

Re-board® Fire Retardant is classified Euroclass C, -s1, -d0 (according to EN 13501-1:2007).



### Sustainability

Re-board® Fire Retardant contains no harmful components and utilizes water-based adhesives. The board can be recycled as paper in normal waste paper streams found throughout the world.





Re-Board® Fire Retardant

### Certified Management Systems

The Norrköping mill is FSC Chain of Custody certified according to FSC-STD-40-004 ver 2.1.

### Certified Management Systems

Re-board® Fire retardant is produced in Norrköping, Sweden.



The mark of responsible forestry

Re-board® Fire Retardant	
Liner grammage (g/m <sup>2</sup> )	410
Width (mm)	1520
Length (mm)	2200, 2400, 3200
Thickness (mm)	16
Weight (kg/sqm)	2.3 (16mm)
Tolerance, corner curvature from flat (mm)	<10
Tolerance in length, general (mm)	± 3

